

INFORMATION SHEET - SUPER GLOSS ENAMEL

DIRECTION FOR USE

Pacific Paints offers a host of High Quality top coats and undercoats for application on various surfaces.

Super Gloss Enamel

This is high quality solvent based enamel that gives a mirror like high gloss finish. It is hard wearing, suitable to use in interiors and is ideal for use on metals, timber, metal and masonry surfaces where a lasting gloss finish is required.

Pacific Roof & Structural Enamel

This is premium, nontoxic, rust-proof paint that gives lasting protection to iron surfaces. It is lead free and harmless to drinking water. Its colours are non fading and rust resistant. For new unweathered galvanized surfaces use of PP-10 Wash Premier is recommended before application of Pacific Roof & Structural Enamel.

Pacific Paving Paint

This is a fast drying paint specially formulated to withstand high wear on floors, passages, steps & patios. It can be walked on within 2 hours of application. Smooth concrete surfaces should be etched with Phosphoric Acid to give the paint a good grip of the surface. The etched surface should be thoroughly washed with water and dried before application of Pacific Paving Paint.

Pacific Premium 100% Acrylic Gloss

A new generation coating that offers the benefits of a Conventional solvent based gloss finish in a water based coating. It has excellent resistance to fungus, is easy to apply, has durability of up to 10 years.

PRIMERS & UNDERCOATS

Antirust Metal Primer

Specially designed to provide protection to steel substrates. Needs to be over coated with an All Purpose Undercoat before application of Super Gloss Enamel.

Galvanised Iron Primer

A waterbase primer specially made for new galvanized iron and aluminium surfaces – as an Undercoat for Super Gloss Enamel.

PP-10 Oruner (One Pack Wash Primer)

A modified resin based primer containing anti-corrosive pigments. This is specially suitable for Galvanized and Aluminium substrates. The acid content reacts with surface of the metal giving a firmly adhered film, which does not chip, flake or crack. For best results over coat with an All Purpose Undercoat before application of finish coats.



INFORMATION SHEET - SUPER GLOSS ENAMEL

Pacific All Purpose Undercoat

An oil base undercoat having excellent filling properties which forms a tough coating. It is to be applied over primer coats and provides an excellent base for finish coats.

Prepare for Perfect results

Proper surface preparation will give you a much better final result and extend the life of the painted surface. When preparing your home for painting, ensure that all loose and flaking paint or foreign matter is removed.

To achieve best results when painting bare timber, fill holes or other surface imperfection with a suitable filler, sand smooth and dust off. Before painting, sanding of previously painted surfaces (particularly enamels) will ensure that subsequent topcoats have better adhesion and last for long time.

To remove blistering or cracked paint: Use a power sander or coarse grade of sandpaper to remove all loose paint. Use fine sandpaper to 'feather' or 'taper' off the edges. Fill the area with suitable exterior filler, sand smooth and dust off. Paint with Pacific with Pacific Paints.

DIRECTIONS FOR USE

Get the right paint for the job

Primers: Prevent corrosion and bond extremely well to bare surfaces enduring good adhesion for all subsequent coats of paint.

Sealers: Seal bare or porous surface, preventing other coats sinking into the surface to provide an even finish for all subsequent coats of paint.

Undercoats: Have good filling characteristics, providing a smooth surface onto which the top coat can be applied.

Acrylic (Water Base): Are ideal for ceilings, interior and exterior walls, pergolas and trim work. They are easy to apply, hard wearing, quick drying, easy to clean up and have excellent adhesion qualities. You have a choice of Gloss or Semi-Gloss silk.

Acrylic Flat Finish: Premium Flat Finish for exterior, interior wall and ceilings. Enamel (Oil Based) are ideally suited to heavy use areas such as door and window trims, as well as wet areas such as bathrooms, laundries, and kitchens.



INFORMATION SHEET - SUPER GLOSS ENAMEL

Get the right amount of paint

Calculate the right amount of paint you need for your job by referring to this chart. (Remember that these quantities are only estimates) Don't forget to reduce the surface area to be painted if the area includes large windows and doors.

Get the right tools for a good job

- It is essential that the right tools are used during preparation and painting of any area.
- Use a quality brush with good bristles, as they hold more paint. This reduces splattering which ensures an even finish.
- When using a roller, choose one that is not too large, as they are heavy once filled with paint. When using the roller you'll need a tray, frame, roller cover and possibly an extension pole.
- A good step ladder is essential when painting. Aluminium ladders are recommended as they are sturdy, yet light to move.
- Don't forget canvas or calico drop sheets. This will minimize mess.
- Sanders and sandpaper should also be used. Sandpaper will only be effective on surfaces in good condition. Sanders will be required if there is significant damage to woodwork.
- Scrapers and knives make filling cracks, corners and holes much easier. These tools are all available from your local stockist.
- Consult your local Pacific Paint stockist if you have any enquiries regarding the necessary tools for your paint jobs as well for other finishes for special jobs.

Cleaning up and disposal

Don't throw any turps away after you have cleaned your brushes in it. Let the sediments in the container settle, then pour off clean turps and reuse it. Remember to store all paints and tools in a secure place out of reach from children.

All chemicals, paints, strippers and other products should be disposed of carefully. They should not be poured down drains, or into cartons. Check with your local council regarding special collection.

Water based or acrylic paints can be safely disposed of with household rubbish if they are dry. Take off the lids and let them dry out thoroughly before putting them in the bin.

