

PACIFIC INFORMATION SHEET

Colour Wood Transtains

COLOUR WOOD TRANSTAIN is an ideal product for toning aesthetic beauty of wood grains. It is fast drying, can be applied by hand wiping as well as spray. It can be over coated with Wood Glow Polyurethane Clear Wood Finishes by brush/spray or with Wood Kote Instant Dry Wood Lacquers by spray. TRANSTAINS are ideally suited for mass production wooden furniture, cabinet making and panelling.

AREAS OF APPLICATION	Wooden Furniture, Cabinet making and Panelling
SUPPLY VISCOSITY	Ready for use. If needed can be reduced with TRANSTAIN REDUCER
SHADES AVAILABLE	As per our colour chart
COVERAGE	Approximately 12sq.m/l
MODE OF APPLICATION	Hand wiping or spray
DRYING TIME	5 minutes touch dry
RECOAT TIME	30 minutes
FINISH	Smooth
THINNER	TRANSTAIN REDUCER
SURFACE PREPARATION	Sandpaper lightly and remove all dust, dirt, etc. to get a smooth surface.

IMPORTANT NOTE

- As different timbers vary considerably in colour, texture, absorption, moisture content and preservative treatment, the colour obtained by using the same colour of Transtain on different timbers would be significantly different. Even on same species of timber, the colour obtained will vary with whether the section is from the heart wood or sapwood. Further, the colour will vary with the thickness of Transtain applied.
- It is of critical importance therefore that prior to stain application on the area to be stained, the Transtain should first be tested on a piece of timber to be used or on part of the job which does not show. If the colour is too strong, lighten it with Transtain Reducer (do not use Min. Turps or other thinners).

