

PRODUCT INFORMATION SHEET

Pacific Acrylic Gloss Finish

Pacific Acrylic Gloss, an innovation in paint technology is the new member added to our 100% acrylic group. It is designed to have long lasting durability with glossy finish. Its excellent alkali resistant & antifungus properties coupled with superior film and levelling characteristics, make it highly recommendable for the protection of exterior building surfaces.

TECHNICAL DATA

AREAS OF APPLICATION	Timber & Timber products, hardboard ply board, Masonite, cement render, plaster, concrete, masonry, blocks, asbestos, cement etc.
SUPPLY VISCOSITY	Ready for use brushing & rolling.
MODE OF APPLICATION	Brush or roll.
COVERAGE	15-17sq. meters per litre
DRYING TIME	Touch dry 15 to 20 minutes
RECOAT TIME	2hours. Minimum
FINISH	Smooth and glossy film.
CLEAN UP THINNER	Water
SURFACE PREPARATION	The surface before painting should be free from dust, dirt, oil, grease, etc. and properly primed.

PRIMERS RECOMMENDED BEFORE APPLICATION OF THIS PRODUCT

TIMBER & TIMBER PRODUCTS	Wood Primer.
HARDBOARDS	All Purpose Undercoat.
CONCRETE, MASONARY, ETC. (dried & cured)	NIL I.e. apply directly without any sealer or primer.
NEW CONCRETE BLOCKS WALLS	Acrylic Block Sealer – Two coats followed by Two coats Acrylic Gloss Finish.