

## PRODUCT INFORMATION SHEET

### **Pacific Acrylic Low Sheen**

Pacific Acrylic Low Sheen is a unique product developed specially for tropical countries. It is based on 100% acrylic emulsion and hence much superior to P.V.A paints in many respects such as resistance to alkali & fungus. Gives outstanding performance on all interior walls and ceilings.

Acrylic Low Sheen finish forms a tough, flexible and adherent film that is resistant to dirt pickup. It retains its colour for a very long time. Acrylic Low Sheen finish is completely washable to give the walls that fresh look year after year.

### **TECHNICAL DATA**

<b>AREAS OF APPLICATION</b>	Plaster, masonry, wood, hardboards, etc.
<b>SUPPLY VISCOSITY</b>	Ready for use, brushing & rolling. (For spraying reduce viscosity with water).
<b>SHADES AVAILABLE</b>	As per colour chart.
<b>MODE OF APPLICATION</b>	Spray, brush or roll
<b>COVERAGE</b>	15-17sq. meters per litre per coat
<b>DRYING TIME</b>	Touch dry 15-20 minutes
<b>RECOAT TIME</b>	2 hours minimum
<b>FINISH</b> Gloss Level	Smooth & Silk Finish 5-12 at 60degrees
<b>CLEAN UP THINNER</b>	Water
<b>SURFACE PREPARATION</b>	The surface before painting should be free from dust, dirt, oil, grease, etc. and suitably primed.

### **PRIMERS RECOMMENDED BEFORE APPLICATION OF THIS PRODUCT**

<b>TIMBER &amp; TIMBER PRODUCTS</b>	Wood Pink Primer
<b>HARDBOARDS</b>	Pacific All Purpose Undercoat
<b>CONCRETE, MASONARY, ETC</b>	Nil I.e. apply directly without any primer or sealer.
<b>NEW CONCRETE BLOCKS WALLS</b>	Acrylic Block Sealer