

PRODUCT INFORMATION SHEET

Pacific Acrylic Roof Paint

Based on 100% pure acrylic emulsion and designed to have long lasting durability with glossary finish PACIFIC ACRYLIC ROOF PAINT is ideal for modern roofs. It is totally non-toxic and hence suitable for roofs that are used for collection of drinking water. All the colour is PACIFIC 100% ACRYLIC ROOF PAINT are light-fast and give adequate hiding in one coat.

TECHNICAL DATA

AREAS OF APPLICATION	Roofs
SUPPLY VISCOSITY	Ready for use brushing & rolling (for spraying reduce viscosity with water)
MODE OF APPLICATION	Brush , Spray or Roll
COVERAGE	15-17sq. meters per litre per coat
DRYING TIME	Touch dry 15-20minutes
FINISH	Smooth & Glossy film
CLEAN UP THINNER	Water
SURFACE PREPARATION	The surface before painting should be free from dust, dirt, oil, grease, etc. and properly primed.

PRIMERS RECOMMENDED BEFORE APPLICATION OF THIS PRODUCT

NEW GALVANISED IRON	Remove oil and grease etc. by wiping with mineral turps. Apply one coat of Pacific Galvo Primer and allow 24hours to dry
----------------------------	--