

PRODUCT INFORMATION SHEET

Pacific All Purpose Undercoat

Pacific All Purpose Undercoat is based on synthetic resins and can be easily applied by brushing or spraying to form a smooth and tough coating. It provides an excellent base for being top coated with synthetic enamels, matt finishes. Etc.

TECHNICAL DATA

AREAS OF APPLICATION	Metals, Wood, Asbestos, Hardboards, Masonite, etc.
SUPPLY VISCOSITY	Ready for use – brushing. (For spraying reduce viscosity with Mineral turps).
SHADES AVAILABLE	White
MODE OF APPLICATION	Brushing or spraying.
DRYING TIME	Surface dry – less than 30 minutes Hard dry – less than 18 hours.
RECOAT TIME	24 hours
COVERAGE	12-14sq. meters per litre per coat
FINISH	Smooth. Matt
CLEAN UP THINNER	Mineral Turps.
FLASH POINT	Above 95°F
SURFACE PREPARATION	The surface before painting should be free from dust, dirt, oil, grease etc. and suitably primed.

PRIMERS RECOMMENDED

On Timber and Timber Products	Wood Primer
On Hardboards	NIL i.e. apply Pacific All Purpose Undercoat direct.
On Cement render etc.	Pacific Cement Sealer
On metals (ferrous)	Pacific Zn Phosphate Red oxide primer