

PRODUCT INFORMATION SHEET

Pacific Cement Sealer

Pacific Cement Sealer, as synthetic resin based product, suited for priming & sealing masonry, cement render, concrete blocks etc. Apart from its sealing properties, it also acts as excellent primer for subsequent finish coats.

TECHNICAL DATA

AREAS OF APPLICATION	Masonry, cement render, concrete blocks
SUPPLY VISCOSITY	Ready for use – brushing, rolling. (For spraying reduce viscosity with Mineral turps.)
SHADES AVAILABLE	White
MODE OF APPLICATION	Brushing, spraying & rolling
COVERAGE	12-14sq. meters per litre per coat
DRYING TIME	Surface dry – less than 2 hours Hard dry – less than 18 hours
RECOAT TIME	24 hours
CLEAN UP THINNER	Minereal Turps
FINISH	Smooth & Matt
FLASH POINT	Above 95°F

SURFACE PREPARATION

NEW UNPAINTED SURFACE	Remove excess sand and other loosely adhering particles etc. with hard wood rubbing block & dust off. The surfaces should be thoroughly dry before application of coatings. A minimum of 28 days should lapse before painting with water based paints and 3 months period if oil based paints are desired.
PREVIOUSLY PAINTED SURFACE	Remove all flaking, peeling paints – sand thoroughly and dust off The cracks & surface imperfections can be filled with mixtures of sand & cement or other suitable filling compounds. Sand smooth the surface & dust off