PRODUCT INFORMATION SHEET

Pacific Natural Wood Stain & Preserver

Pacific Natural Wood Stain & Preserver, available in light fast and weather resistant colours, high lights the aesthetic beauty of the wood grains. It protects the wood against rotting, fungi and insects by its combined moisture regulating action, deep penetrating power and water repellent properties. Ideally suited for domestic and tropical woods, windows and outdoors.

TECHNICAL DATE

AREAS OF APPLICATION	Wooden houses, external claddings, roof under lays, windows, shutters, door, fences, garden
	furniture etc.
SUPPLY VISCOSITY	Ready for use
SHADES AVAILABLE	As per our special colour chart
COVERAGE	10sq. meters per litre per coat
MODE OF APPLICATION	Brush, spray or dip
DRYING TIME	Touch dry: generally 2-3 hours . The drying may
	be retarded in the case of low absorbing woods
	& hard boards, weather conditions may also
	affect the drying.
RECOAT TIME	24 hours
FINISH	Smooth and eggshell finish
CLEAN UP THINNER	Minerals Turps.

SURFACE PREPARATION

ON NEW UNPAINTED SURFACES	Rub all the wood with sand paper and remove
	dust, dirt, etc.
ON PREVIOUSLY PAINTED	Remove all flaking, peeling paint by scraping,
	sand thoroughly and dust off.
PRIMERS RECOMMENDED	Nil- Generally 2 coats of Pacific Solid Wood Stain
	& Preserver are recommended. On soft wood
	with non-uniform absorption three coats may be
	applied.

