

PRODUCT INFORMATION SHEET

Pacific Satin Enamel

Pacific Satin Enamel, based on Alkyd Resins, dries to give a beautiful even semi-gloss finish, suited for interior and as well as the sheltered areas of exterior. It dries to hard wearing and cleanable surface. Its typical uses are on walls, window frames, ceilings, furniture, bathroom, laundries and in kitchen etc.

TECHNICAL DATA

AREAS OF APPLICATION	Wood, hardboards & metal.
SUPPLY VISCOSITY	Ready for use brushing & rolling. (For spraying. Reduce viscosity with Mineral Turps.)
SHADES AVAILABLE	As per colour chart.
MODE OF APPLICATION	Brush, roll or spray.
COVERAGE	15-17sq. meters per litre per coat.
DRYING TIME	Surface dry – 3hrs, Hard dry – 18hrs
RECOAT TIME	24hours
FINISH	Smooth satin like semi glossy finish.
CLEAN UP THINNER	Mineral Turps
SURFACE PREPARATION	The surface before painting should be free from dust, dirt, oil, grease, etc. and appropriately primed.

PRIMERS RECOMMENDED BEFORE APPLICATION OF THIS PRODUCT

TIMBER & TIMBER PRODUCTS	Wood Primer.
HARD BOARDS	Pacific All Purpose Undercoat.
IRON & STEEL	Pacific Red ox Zn Phosphate Primer.