

## PRODUCT INFORMATION SHEET.

### **Pacific Super Paving Paint**

Based on single pack polyurethane resins, Pacific Super Paving Paint is the best pick, while protection against hardware fast traffic is required. Suited for interior & exterior purposes, it dries quickly to give remarkably hardwearing glossy films.

<b>AREAS OF APPLICATION</b>	Floorings, footsteps, paths, etc.
<b>SUPPLY VISCOSITY</b>	Ready for use, brushing and rolling. (For spraying reduce viscosity with Mineral turps.
<b>SHADES AVAILABLE</b>	As per our colour chart.
<b>MODE OF APPLICATION</b>	Spray, Brush or Roll
<b>COVERAGE</b>	15-16sq. meters per litre per coat.
<b>DRYING TIME</b>	Tack free-4 hours.
<b>RECOAT</b>	Overnight
<b>FINISH</b>	Smooth & glossy films.
<b>CLEAN UP THINNER</b>	Minerals Turps.

### SURFACE PREPARATION

<b>ON TIMBER FLOORS</b>	Ensure that the surface to be painted is free from dust, grease, oil, dirt etc. by sand papering. Apply 1 coat of wood pink primer and allow drying for 24 hours. Fill the cracks, imperfections with putty, sand smooth, when dry. Apply 2 coats of Pacific Super Paving Paint allowing 24 hours gap between each coat. When previously paint surfaces are to be painted all the flaking, peeling paint etc. are to be removed before application of primer.
<b>ON CONCRETE FLOORS</b>	Ensure that the surface to be painted is properly cured & dried. For smooth concrete floors which are usually trowelled, etching the surface with dilute acid is recommended. Excess sand, dust dirt & other loosely adhering particles are to be removed. In the case of previously painted surfaces ensure that the flaking, peeling paint etc. are removed and the surface is sanded properly.