

# PACIFIC ACRYLIC TEXTURE FINISH 380 – SAND FREE

## PREMIUM INTERIOR / EXTERIOR FINISH

### PRODUCT DESCRIPTION

It is a high build Pure Acrylic emulsion based coating which is applied as thicker film than conventional paints. It has good protective properties and enhances the beauty of the substrates. Enables to mask minor defects in the substrate.

### AREAS OF APPLICATION

Concrete Walls, Beams, Ceiling, plaster asbestos, hardboards, plywood and Masonite surfaces.

### TECHNICAL DATA

<b>COLOUR RANGE</b>	Normally available in white. Factory tinted light pastel colours can be given on request. Can be over coated with desired colour Paints.
<b>FINISH</b>	Flat textured profile
<b>TOXICITY</b>	Non Toxic and lead free
<b>THINNING &amp; CLEAN UP</b>	Water
<b>COVERAGE</b>	1-2sq. meter/litre per coat. Practical coverage may depend on surface profile, method of application.
<b>DRYING TIME (at 25°C &amp; RH 60%)</b>	Touch Dry : 1 hour
<b>RECOAT TIME</b>	24 hours
<b>PACKS AVAILABLE</b>	4L, 1L

### APPLICATION

<b>METHOD OF APPLICATION</b>	Suitable spray equipment or texture rollers
<b>SURFACE PREPARATION</b>	The surface must be free of dust mould grease, oils efflorescence, fungi, stains, rust and mastic compounds.
<b>APPLICATION</b>	A minimum of 30 days curing is required for proper curing of alkaline substrates. Cracks and flaws should be filled with quality fillers. Blow holes and pin holes to be spot prime and filled with texture coating. Apply one coat of Acrylic Sealer undercoat. Allow 4 hours drying time then apply one coat of texture finish. Then allow 24 hours drying time. Apply second coat of texture finish or one coat of 100% Flat Tinted to desired colour.