

PRODUCT INFORMATION SHEET

Pacific Anti-Rust Primer

Tractor Anti-rust Primer is based on synthetic resins & corrosion inhibiting pigments offers good corrosion resistance at an economical price and hence serves as a good quality shop primer. Widely used for painting of under chassis of transport vehicles, Pacific Anti-rust primer can be easily applied by a brush and it dries hard to give a good adherent coating.

TECHNICAL DATA

AREAS OF APPLICATION	Ferrous substrates like metal structures etc.
SUP VISCOSITY	Ready for use, brushing (For spraying reduce viscosity with mineral turps.)
SHADES AVAILABLE	Red oxide & Grey.
MODE OF APPLICATION	Brushing or spraying.
COVERAGE	16-18sq. meters per litre.
DRYING TIME	Surface dry- less than 1 hour Hard dry-less than 18 hours.
RECOAT TIME	24 hours.
CLEAN UP THINNER	Mineral Turps.
FLASH POINT	95°C

SURFACE PREPARATION

NEW UNPAINTED SURFACE	Ensure that the surface to be painted is free from all flaking, peeling paint, rust. Mill-scale, oil, grease etc. By wire brushing or by using other hand tools.
DIRECTIONS FOR USE	Surface that's prepared is to be then coated with Pacific anti-rust primer within 24 hours. Followed by Pacific all-purpose undercoat. Ensure that the 24 hours gap is given between each coat.