

PRODUCT INFORMATION SHEET

PACIFIC FENCE FINISH

(EXTERIOR)

PRODUCT DESCRIPTION

It is an economical fence stain which is semi-transparent. It is particularly recommended for rough sawn timber where ease of application and quick drying are essential.

TECHNICAL DATA

AREAS OF APPLICATION	Rough sawn and semi-finished timber fence
COLOUR RANGE	As per colour card
GLOSS LEVEL AT 60° HEAD	5-10%
SOLVENT RESESTANCE	Being a thermoplastic film sensitive towards alcohol and aromatic hydrocarbons
TOXICITY	Dry film is non-toxic and lead free
THINNING & CLEAN UP	Water
COVERAGE	12sq.m/l per coat. Practical Coverage may depend on surface Profile, method of application and weather conditions.
DRYING TIME (at 25°C & RH 60%)	Touch dry – 20 minutes
RECOAT	2 hours
PACK AVAILABLE	20L, 4L & 1L
CONFORMS TO SPECIFICATION	-

APPLICATION

METHOD OF APPLICATION	Brush and Roller
SURFACE PREPARATION	Remove all dirt, dust, loose flaking paint by thoroughly cleaning the surface
APPLICATION	Stir the contents thoroughly before and during use with abroad flat stirring using an upward lifting action. Apply two even coats direct from the can by convenient method of application. Keep in mind little bit of water could be used for ease of application.
FLAMMABILITY & TRANSPORT INFORMATION	Non-flammable
SAFETY PRECAUTION	Do not apply at temperature below 10°C. Provide adequate ventilation during use. Keep out of reach of children. Check cross cut adhesion of old paint before repainting. In normal conditions, a week's curing is required to develop full hardness and resistance properties.

