

# PACIFIC PIGMENTED SEALER

## EXTERIOR / INTERIOR

### PRODUCT DESCRIPTION

It is oil based sealer made from synthetic resins. It has excellent filling properties and forms a smooth tough coating. It provides an excellent base for finish coats.

### AREAS OF APPLICATION

It is suitable for priming and sealing of masonry, cement render wall boards, weatherboards, concrete blocks.

### TECHNICAL DATA

<b>COLOUR RANGE</b>	White, May be tinted with Machine Colorant
<b>GLOSS LEVEL OF 60 HEAD</b>	15%
<b>SOLVENT RESISTANCE</b>	Alcohols & Polar Solvents may attack the film
<b>TOXICITY</b>	Dry film is non-toxic
<b>THINNING &amp; CLEAN UP</b>	Thinner for Enamel 600 / Mineral turps.
<b>COVERAGE</b>	10sq.meter/ litre per coat. Practical Coverage may depend on surface profile, method of application and weather conditions.
<b>DRYING TIME (at 25°C &amp; RH 60%)</b>	Touch dry : 2 hours
<b>RECOAT TIME</b>	16 hours
<b>PACKS AVAILABLE</b>	4L & 1L

### APPLICATION

<b>METHOD OF APPLICATION</b>	Brush, Roller or Spray
<b>SURFACE PREPARATION</b>	All surfaces must be dry, clean and free from all loose, dirt, wax, grease, mould, mildew and flaking paint.
<b>APPLICATION</b>	Stir the contents thoroughly before and during use with a broad flat stirrer, using an upward lifting action. Apply one coat by convenient method of application. Brushing is best as this works well into the substrate. Normally apply direct from the can but for ease of application add 5% thinner.