

PACIFIC PIGMENTED SEALER

EXTERIOR / INTERIOR

PRODUCT DESCRIPTION

It is an oil based sealer made from synthetic resins. It has excellent filling properties and forms a smooth tough coating. It provides an excellent base for finish coats.

AREAS OF APPLICATION

It is suitable for priming and sealing of masonry, cement render wall boards, weather boards, concrete blocks.

TECHNICAL DATA

COLOUR RANGE	White. May be tinted with Machine Colorant
GLOSS LEVEL AT 60C HEAD	0.5%
SOLVENT RESISTANCE	Alcohols & Polar Solvents may attack the film
TOXICITY	Dry Film is non-toxic and lead free
THINNING & CLEAN UP	Thinner for enamel 600 / Mineral Turps.
COVERAGE	10sq.m/l per cost Practical coverage may depend on surface profile, method of application and weather Conditions.
DRYING TIME (at 25°C & RH 60%)	Touch dry : 2 hour
RECOAT	16 hours
PACKS AVAILABLE	4L. 1L. 20L

APPLICATION

METHOD OF APPLICATION	Brush, Roller or spray
SURFACE PREPARATION	All surfaces must be dry, clean and free from all loose, dirt, Wax, grease, mould, mildew and loose and flaking paint.
APPLICATION	Stir the contents thoroughly before and during use with a Broad flat stirrer. Using an upward lifting action. Apply one coat by convenient method of application. Brushing is best as this works well into the substrate. Normally apply direct from the can but for ease of Add 5% thinner.
FLAMMABILITY & TRANSPORTATION INFORMATION	Highly flammable. Dangerous goods clause 3.2. Flash Paint 32c UN 1263 PG 111. Keep away from sources of ignition.
SAFETY & PRECAUTIONS	Do not apply at temperature below 10°C. Provide adequate ventilation during use. Keep out of reach of children. Check cross cut adhesion of old paint before Repainting. In normal condition a week's curing is required to develop full hardness & resistance properties.