

PRODUCT INFORMATION SHEET

Pacific Roof Enamel

Pacific Roof Enamel is based on synthetic resins and is specially formulated for modern roofs. It is totally lead-free, non-poisonous and hence harmless to drinking water. All the colours in Roof Enamel are light fast and give adequate hiding in one coat. Roof Paint Aluminium reflects the sun and heat and keeps the house cool.

AREAS OF APPLICATION	Roofs.
SUPPLY VISCOSITY	Ready for use brushing & rolling (for spraying reduce viscosity with Mineral turps.
SHADES AVAILABLE	As per colour chart.
MODE OF APPLICATION	Brush, spray or roll.
COVERAGE	16-18sq.meters per litre per coat.
DRYING TIME	Surface dry – less than 3 hours. Hard dry – less than 18 hours.
RECOAT TIME	24 hours
CLEAN UP THINNER	Mineral Turps
FLASH POINT	Above 95°F
SURFACE PREPARATION New unpainted Surface	Remove oil, grease, dirt etc. by wire brushing or solvent cleaning, etc. dust-off.
PREVIOUSLY PAINTED	Remove all flaking, peeling paints, rust, mill scale, oil grease etc. By wire brushing etc. Dust off.
RECOMMENDED PRIMER	Pacific PP-10 washes primer or if substrate is in good condition anti rust primer.