

PRODUCT INFORMATION SHEET

Pacific Super Gloss Synthetic Enamel

Pacific Super Gloss Synthetic Enamel is for those who want the best. It is the enamel with a perfect finish and a hard mirror like gloss that repels water and sun, dust and moisture. Its brush ability is par excellence. In exterior use and rugged weather conditions. Pacific Super Gloss Synthetic Enamel is difficult to beat. It is extensively used and recommended for truck fleets, transport coaches, machinery and equipment, furniture and fixtures, shinning signboards, doors & windows, fixtures etc. Pacific Brilliant White is truly the white that stays white for years. Pacific Super Gloss Synthetic Enamel has such an excellent levelling property that it is difficult to distinguish a brushed surface from a sprayed surface.

SURFACE TO BE PAINTED	Metals, wood, plaster and a variety of other surfaces.
SUPPLY VISCOSITY	Ready for use brushing and rolling (for spraying reduce viscosity with mineral turps).
SHADES AVAILABLE	As per colour chart.
MODE OF APPLICATION	Rolling, brushing, spraying.
COVERAGE	16-18sq.meters per litre per coat, some shades like P.O. Red give slightly less covering.
DRYING TIME	Surface dry - less than 3 hours. Hard dry – less than 18 hours.
RECOAT TIME	24 hours.
CLEAN UP THINNER	Mineral Turps.
FLASH POINT	Above 95°F.
SURFACE PREPARATION	The surface before painting should be free from dust, dirt, oil, grease, etc. and appropriately primed.

PRIMERS RECOMMENDED BEFORE APPLICATION OF THIS PRODUCT

TIMBER & TIMBER PRODUCTS	Wood pink primer followed by Pacific all-purpose Undercoat.
HARDBOARDS, ETC.	Pacific all-purpose Undercoat.
CEMENT RENDER, PLASTER, ETC. (cured & dried)	Deco Seal all-purpose Sealer followed by Pacific all-purpose Undercoat.
IRON & STEEL	Pacific red oxide primer followed by all-purpose Undercoat.
ALUMINIUM	Vinyl Etch Primer or PP-10 one pack washes primer.