

PRODUCT INFORMATION SHEET

Wood Gloss Polyurethane Sanding Sealer

Interior Brushing

Wood Glow Polyurethane Sanding Sealer is a high quality, polyurethane based Clear Sanding Sealer. It is fast drying and has excellent abrasion resistance and can be applied by brush.

AREAS OF APPLICATION	Interior painting only on dressed timber furniture doors, veneers, wall panelling etc. As a sealer coat before finish coat is applied.
SUPPLY VISCOSITY	Ready to use, brushing (For spraying reduce Viscosity with Min. Turps.
RECOMMENDED THINNER FOR SPRAY & CLEAN UP	Min Turps
MODE OF APPLICATION	Brush or Spray
COVERAGE	12sq meter/litre per coat. Practical Coverage may depend upon surface profile, method of application and weather conditions.
DRYING TIME	Surface dry / Touch – 30 minutes Tack Free – 3 – 4 hrs. Hard dry – Overnight
RECOAT TIME	Minimum 3 hours
DIRECTION FOR USE	Thoroughly sand paper the surface to smooth finish and dust off. Remove all wax, grease by cleaning with thinner. Stir the Contents thoroughly before use with a broad flat stirrer using an upward lifting action. Apply by brush or spray. Sand with fine sand paper before application next Coat.