

## PRODUCT INFORMATION SHEET

### Wood Glow Polyurethane Clear Wood Finish

#### Gloss/Semi-Gloss/Matt/White Pine

Wood Glow Polyurethane Clear Wood Finish is a fast drying and hardwearing coating, ideally suited for interior timber, panels, furniture, doors etc. It yields a long lasting abrasion resistant finish. Based on one pack polyurethane resin, the films obtained by it are tough and durable.

<b>AREAS OF APPLICATION</b>	Timber, furniture, doors, veneers, wall panellings, plywoods etc.
<b>SUPPLY VISCOSITY</b>	Ready for use, brushing. (For spraying reduce viscosity with Mineral turps. )
<b>RECOMMENDED THINNER FOR SPRAY &amp; CLEAN UP</b>	Mineral Turps
<b>MODE OF APPLICATION</b>	Brush or Spray
<b>RECOMMENDED APPLICATION VISCOSITY FOR SPRAYING</b>	25 to 30 seconds (at a pressure of 40-50psi)
<b>COVERAGE</b>	14-16sq.meters per litre per coat
<b>FINISH AVAILABLE</b>	Gloss/Semi-gloss/Matt/White Pine
<b>DRYING TIME</b>	Surface dry – 15 – 20 minutes Tack free – 2 – 3 hours Hard dry – Overnight
<b>RECOAT</b>	12 hours

### DIRECTION FOR USE

#### REPAINTING

- Thoroughly sand paper the surface to smooth finish and dust off. Apply 1 or 2 coats of the desired finish – Clear gloss, semi-gloss or matt. Allow 12 hours drying between each coat.

#### NEW SURFACE

- Thoroughly sand paper the surface to smooth finish and dust off. Apply 1 coat of Wood Glow Sanding Sealer (clear). Lightly sand after 2hrs drying. Then apply 2 coats of the desired finish – clear gloss, semi-gloss or matt allowing 12 hours drying between each coat.